## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-187628

(43) Date of publication of application: 22.07.1997

(51)Int.Cl.

B01D 63/02 B01D 63/00

(21)Application number: 08-094697 (22)Date of filing:

26.03.1996

(71)Applicant: NIKKISO CO LTD

(72)Inventor: SASAHARA SHIGERU

OHARA SUMIO

(30)Priority

Priority number: 07305173


Priority date: 31.10.1995 Priority country: JP

## (54) HOLLOW FIBER TYPE MODULE AND ITS PRODUCTION

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain a hollow fiber. module which reduce the occurrence of concn. polarization and has high removal efficiency by adhering and fixing one end of a hollow fiber bundle by a resin compsn., sealing the open ends of the hollow holes of respective hollow fibers and opening and providing a supporting section formed of the resin compsn. with apertures communicating with the outside of the hollow fibers

SOLUTION: The hollow fiber bundle 5 is housed in a cylindrical casing 4 provided with a closing cap 2 having an injection port 21 for injecting an original liquid to be treated at one end and a closing cap 3 having a discharge port 31 out of which the treated filtrate flows at



the other end. The sealing side supporting section 6 for sealing the opening ends of the hollow holes of the respective hollow fibers 51 is formed by adhering and fixing the one end of the hollow fiber bundle 5 at one end of the injection port 21 side in the cylindrical casing 4. The open side supporting section 7 is formed at the other end on the discharge port 31 side in